

LightWise®




OPENSTRIP LIGHT

DESCRIPTION

CATALOG	ELECTRONIC BALLAST	LAMP TYPE	NO. OF LAMPS
DL423	DXE2H8	F25/30T8	2

ELECTRICAL CHARACTERISTICS

INPUT VOLTAGE	INPUT CURRENT	INPUT WATTS	FREQUENCY
120V	0.56A	58.5W	60HZ



PHYSICAL DIMENSIONS

UNITS	M	L	W	H
INCHES	34.60"	36.09"	4.17"	3.35"
TOL(+/-)	0.05	0.05	0.05	0.05

CARTON DIMENSIONS

UNITS	L	W	H
INCHES	36.61"	4.72"	2.05"

FEATURES

- Factory mounted, pre-wired sockets cut installation time.
- Hinging/locking lamp bracket cuts installation time.
- 1 quarter-turn fastener secures wireway cover to housing.
- Channel connector furnished for continuous row applications.
- Ballast secured by 2 captive bolts and nuts to ensure tight, reliable fit for maximum heat dissipation and minimal ballast noise.
- All parts painted after fabrication to facilitate installation, increase efficiency, and inhibit rusting.

SPECIFICATIONS

- HOUSING - 22 Ga. die formed C.R.S. or optional .040" aluminum.
- FINISH - white powder coating with 5-stage iron/phosph prepared metal. 92% minimum average reflectance.
- ELECTRICAL - electronic ballast standard, rated Class
- LABELS - UL listed as fluorescent fixture suitable for damp locations. CUL listing for Canada available - consult factory.
- MOUNTING - surface or suspended.

PRODUCT PHOTO

